

S220 鎢鋼圓鼻銑刀- 小柄/標準型- 2刃

S220 MICRO GRAIN CARBIDE END MILLS- Corner Radius- 2F


· CECRM2000000A

· CECR2000000A

刃徑 d	公差 Tolerance
$\phi < 3$	0 ~ -0.02
$3 \leq \phi \leq 10$	-0.01 ~ -0.03
$10 < \phi$	-0.01 ~ -0.04

半徑 R	公差 Tolerance
R	±0.02

超精銑 Bright Finishing	—
精銑 Finishing	○
中銑 Semi Finishing	◎
粗銑 Roughing	◎



NEW
SIZE

08

刃徑 d	R角 R	刃長 L1	全長 L	柄徑 D	刃數 F	白刀訂購編號 Uncoated Order No.	鍍膜訂購編號 Coated Order No.
1.0	0.2R	2	50	4	2	CECRM2010002	CECRM2010002A
1.0	0.3R	2	50	4	2	CECRM2010003	CECRM2010003A
1.5	0.2R	3	50	4	2	CECRM2015002	CECRM2015002A
1.5	0.3R	3	50	4	2	CECRM2015003	CECRM2015003A
2.0	0.2R	4	50	4	2	CECRM2020002	CECRM2020002A
2.0	0.3R	4	50	4	2	CECRM2020003	CECRM2020003A
2.5	0.2R	5	50	4	2	CECRM2025002	CECRM2025002A
2.5	0.3R	5	50	4	2	CECRM2025003	CECRM2025003A
2.5	0.5R	5	50	4	2	CECRM2025005	CECRM2025005A
3.0	0.2R	6	50	4	2	CECRM2030002	CECRM2030002A
3.0	0.3R	6	50	4	2	CECRM2030003	CECRM2030003A
3.0	0.5R	6	50	4	2	CECRM2030005	CECRM2030005A
3.0	1.0R	6	50	4	2	CECRM2030010	CECRM2030010A
4.0	0.3R	8	50	4	2	CECRM2040003	CECRM2040003A
4.0	0.5R	8	50	4	2	CECRM2040005	CECRM2040005A
4.0	1.0R	8	50	4	2	CECRM2040010	CECRM2040010A
4.0	0.3R	8	50	6	2	CECR2040003	CECR2040003A
4.0	0.5R	8	50	6	2	CECR2040005	CECR2040005A
4.0	1.0R	8	50	6	2	CECR2040010	CECR2040010A
5.0	0.5R	10	50	6	2	CECR2050005	CECR2050005A
5.0	1.0R	10	50	6	2	CECR2050010	CECR2050010A
6.0	0.5R	12	50	6	2	CECR2060005	CECR2060005A
6.0	1.0R	12	50	6	2	CECR2060010	CECR2060010A
8.0	0.5R	16	60	8	2	CECR2080005	CECR2080005A
8.0	1.0R	16	60	8	2	CECR2080010	CECR2080010A
8.0	1.5R	16	60	8	2	CECR2080015	CECR2080015A
10.0	0.5R	20	75	10	2	CECR2100005	CECR2100005A
10.0	1.0R	20	75	10	2	CECR2100010	CECR2100010A
10.0	1.5R	20	75	10	2	CECR2100015	CECR2100015A
10.0	2.0R	20	75	10	2	CECR2100020	CECR2100020A
12.0	0.5R	24	75	12	2	CECR2120005	CECR2120005A
12.0	1.0R	24	75	12	2	CECR2120010	CECR2120010A
12.0	1.5R	24	75	12	2	CECR2120015	CECR2120015A
12.0	2.0R	24	75	12	2	CECR2120020	CECR2120020A

→ 切削條件表
Cutting Condition P.538

→ 技術資料
Technical Data P.622

S220

S220 Carbide End Mills

S220 鎢鋼銑刀系列

Table 07

S220 鎢鋼圓鼻銑刀- 2刃(鍍膜) 切削條件表

SOLID CARBIDE END MILLS- CUTTING CONDITION TABLE

加工材質 Material	碳素鋼 Carbon Steels		合金鋼 Alloy Steels		合金鋼 Alloy Steels		調質鋼 Hardened Steels		調質鋼 Hardened Steels		不銹鋼 Stainless Steels		鑄鐵 Cast Iron	
工件料號 Material Code	S35C,S45C,S50C		SCM,SKT,SKD		SCM,SKT,SKD		SKT,SKD		SKT,SKD		SUS304		FC,FCD	
硬度 Hardness	HRC<20		HRC20~30		HRC30~45		HRC45~55		HRC55~63		—		HRC<30	
切削速度 Vc	95m/min		75m/min		63m/min		38m/min		28m/min		75m/min		110m/min	
外徑 Diameter	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)
1mm	22,400	140	19,150	110	16,130	70	8,960	60	6,720	40	19,150	110	28,220	300
2mm	12,100	180	9,680	140	8,060	100	4,840	70	3,630	50	9,680	140	14,110	330
3mm	8,460	180	6,450	150	5,240	100	3,360	70	2,500	50	6,450	150	9,680	330
4mm	6,050	180	4,840	150	4,030	110	2,420	70	1,820	60	4,840	150	7,260	330
5mm	5,040	200	3,830	150	3,220	110	2,020	80	1,510	60	3,830	150	5,650	360
6mm	4,030	200	3,220	150	2,620	110	1,620	80	1,210	60	3,220	150	4,840	400
8mm	3,020	200	2,420	180	2,020	120	1,210	80	900	60	2,420	180	3,630	400
10mm	2,420	200	1,910	180	1,620	140	980	80	730	60	1,910	180	2,820	420
12mm	2,020	200	1,620	180	1,340	140	810	80	610	60	1,620	180	2,420	450
14mm	2,020	220	1,520	190	1,280	140	810	90	610	60	1,520	190	2,240	500
16mm	1,740	250	1,340	200	1,120	160	700	100	530	70	1,340	200	2,020	540
18mm	1,740	250	1,180	200	980	160	700	100	530	70	1,180	200	1,790	540
20mm	1,340	250	1,070	200	900	160	540	100	400	70	1,070	200	1,570	540
切削量 Cutting Amount (mm)	Ap=0.5D (D<3, Ap≤0.25D)				Ap=0.1D (D<3, Ap≤0.05D)				Ap=0.5D (D<3, Ap≤0.25D)				Ap=0.5D (D<3, Ap≤0.25D)	
														

Table 08

S220 鎢鋼圓鼻銑刀 / S220 鎢鋼長柄型圓鼻銑刀- 4刃(鍍膜) 切削條件表

SOLID CARBIDE END MILLS- CUTTING CONDITION TABLE

加工材質 Material	碳素鋼 Carbon Steels		合金鋼 Alloy Steels		合金鋼 Alloy Steels		調質鋼 Hardened Steels		調質鋼 Hardened Steels		不銹鋼 Stainless Steels		鑄鐵 Cast Iron	
工件料號 Material Code	S35C,S45C,S50C		SCM,SKT,SKD		SCM,SKT,SKD		SKT,SKD		SKT,SKD		SUS304		FC,FCD	
硬度 Hardness	HRC<20		HRC20~30		HRC30~45		HRC45~55		HRC55~63		—		HRC<30	
切削速度 Vc	94m/min		75m/min		63m/min		37m/min		28m/min		75m/min		110m/min	
外徑 Diameter	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)	S (rpm)	F (mm/min)
3mm	5,040	550	6,450	380	5,240	180	3,380	220	2,580	170	6,450	380	9,680	1,010
4mm	6,050	550	4,840	380	4,030	180	2,420	220	1,820	170	4,840	380	7,260	1,210
5mm	5,040	550	3,830	380	3,220	180	2,020	220	1,510	170	3,830	380	5,650	1,210
6mm	4,030	550	3,220	380	2,620	180	1,620	220	1,210	170	3,220	380	4,840	1,210
8mm	3,020	550	2,420	380	2,020	200	1,210	220	900	170	2,420	380	3,630	1,210
10mm	2,420	570	1,910	400	1,620	200	960	230	730	180	1,910	400	2,820	1,310
12mm	2,020	570	1,920	400	1,340	200	810	230	610	180	1,620	400	2,420	1,410
14mm	2,020	620	1,520	450	1,280	220	810	260	610	190	1,520	450	2,240	1,570
16mm	1,740	670	1,340	470	1,120	220	700	270	530	200	1,340	470	2,020	1,680
18mm	1,570	670	1,180	470	980	220	620	270	470	200	1,180	470	1,790	1,680
20mm	1,340	670	1,070	470	900	220	540	270	400	200	1,070	470	1,570	1,790
切削量 Cutting Amount (mm)	Ap=1.5D Ap≤0.1D				Ap=1D Ae≤0.05D				Ap=1.5D Ae≤0.1D				Ap=1.5D Ae≤0.1D	
														

※ 切削公式 Cutting Formula : S(主軸轉速) = Vc(切削速度) × 1000 / D(外徑) / π (3.14) F(進給速度) = fz(每刃進給量) × Z(刃數) × S(主軸轉速)

- 當加工聲音尖銳時，請調降主軸轉速(S) (10~40%)。When the sound is piercing, please lower the spindle speed(S) (10~40%).
- 當機台震動太大時，請調降進給速度(F) (10~40%)。When the machine is vibrating, please decrease the feed rate(F) (10~40%).
- 當主軸負載太大時，請調降進給速度(F) (10~40%)。When the spindle load is high, please decrease the feed rate(F) (10~40%).
- 以上數據為建議值，適當的條件仍需視機台狀況，夾治具品質，潤滑冷卻系統...等而改變。

These are recommended values which depend on the condition of the machine, fixture, lubricating & cooling systems... etc. They may have to be adapted.