

## N620 NANO CARBIDE END MILLS- Ball Nose- Long Shank- 2F

|                      |   |
|----------------------|---|
| 超精銑 Bright Finishing | ○ |
| 精銑 Finishing         | ◎ |
| 中銑 Semi Finishing    | ○ |
| 粗銑 Roughing          | — |



39


➡ 切削條件表 P.554  
Cutting Condition

→ 技術資料 P.622  
Technical Data

Table 39

N620 奈米鎢鋼短刃型 / 短刃長柄型球刀- 2刃(鍍膜) 切削條件表

## SOLID CARBIDE END MILLS- CUTTING CONDITION TABLE


| 加工材質<br>Material              | 合金鋼<br>Alloy Steels                                                                                       |               | 合金鋼<br>Alloy Steels |               | 調質鋼<br>Hardened Steels |               | 調質鋼<br>Hardened Steels |               | 鑄鐵<br>Cast Iron |               |
|-------------------------------|-----------------------------------------------------------------------------------------------------------|---------------|---------------------|---------------|------------------------|---------------|------------------------|---------------|-----------------|---------------|
| 工件料號<br>Material Code         | SCM,SKT,SKD                                                                                               |               | SCM,SKT,SKD         |               | SKT,SKD                |               | SKT,SKD                |               | FC,FCD          |               |
| 硬度<br>Hardness                | HRC20~30                                                                                                  |               | HRC30~45            |               | HRC45~55               |               | HRC55~63               |               | HRC<30          |               |
| 切削速度 Vc                       | 230m/min                                                                                                  |               | 180m/min            |               | 140m/min               |               | 110m/min               |               | 230m/min        |               |
| 半徑<br>R                       | S<br>(rpm)                                                                                                | F<br>(mm/min) | S<br>(rpm)          | F<br>(mm/min) | S<br>(rpm)             | F<br>(mm/min) | S<br>(rpm)             | F<br>(mm/min) | S<br>(rpm)      | F<br>(mm/min) |
| 0.5R                          | 32,000                                                                                                    | 2,000         | 32,000              | 2,000         | 32,000                 | 1,700         | 32,000                 | 1,360         | 32,000          | 2,000         |
| 1.0R                          | 32,000                                                                                                    | 3,060         | 28,660              | 3,020         | 22,290                 | 1,870         | 17,520                 | 1,490         | 32,000          | 3,060         |
| 1.5R                          | 24,420                                                                                                    | 3,400         | 19,110              | 2,720         | 14,860                 | 1,700         | 11,680                 | 1,360         | 24,420          | 3,400         |
| 2.0R                          | 18,310                                                                                                    | 3,100         | 14,330              | 2,510         | 11,150                 | 1,620         | 8,760                  | 1,280         | 18,310          | 3,100         |
| 2.5R                          | 14,650                                                                                                    | 2,980         | 11,470              | 2,250         | 8,920                  | 1,450         | 7,010                  | 1,150         | 14,650          | 2,980         |
| 3.0R                          | 12,210                                                                                                    | 2,850         | 9,550               | 1,960         | 7,430                  | 1,320         | 5,840                  | 1,060         | 12,210          | 2,850         |
| 4.0R                          | 9,160                                                                                                     | 2,420         | 7,170               | 1,740         | 5,570                  | 1,150         | 4,380                  | 890           | 9,160           | 2,420         |
| 5.0R                          | 7,330                                                                                                     | 2,170         | 5,730               | 1,530         | 4,460                  | 980           | 3,500                  | 750           | 7,330           | 2,170         |
| 6.0R                          | 6,100                                                                                                     | 2,040         | 4,780               | 1,400         | 3,720                  | 820           | 2,920                  | 680           | 6,100           | 2,040         |
| 切削量<br>Cutting Amount<br>(mm) | Ap=0.02D<br>Pf=0.05D<br> |               |                     |               |                        |               |                        |               |                 |               |

※ 切削公式 Cutting Formula : S(主軸轉速) = Vc(切削速度) × 1000 / D(外徑) / π (3.14)      F(進給速度) = fz(每刃進給量) × Z(刃數) × S(主軸轉速)

Table 40

N620 奈米鎢鋼短刃長頸型銑刀- 2刃(鍍膜) 切削條件表

## SOLID CARBIDE END MILLS- CUTTING CONDITION TABLE

| 加工材質<br>Material              | 合金鋼<br>Alloy Steels                                                                 |               |            | 合金鋼<br>Alloy Steels |               |            | 調質鋼<br>Hardened Steels |               |            | 調質鋼<br>Hardened Steels |               |            | 鑄鐵<br>Cast Iron |               |            |
|-------------------------------|-------------------------------------------------------------------------------------|---------------|------------|---------------------|---------------|------------|------------------------|---------------|------------|------------------------|---------------|------------|-----------------|---------------|------------|
| 工件料號<br>Material Code         | SCM,SKT,SKD                                                                         |               |            | SCM,SKT,SKD         |               |            | SKT,SKD                |               |            | SKT,SKD                |               |            | FC,FCD          |               |            |
| 硬度<br>Hardness                | HRC20~30                                                                            |               |            | HRC30~45            |               |            | HRC45~55               |               |            | HRC 55~63              |               |            | HRC<30          |               |            |
| 切削速度 Vc                       | 59m/min                                                                             |               |            | 59m/min             |               |            | 42m/min                |               |            | 25m/min                |               |            | 67m/min         |               |            |
| 外徑<br>Diameter                | S<br>(rpm)                                                                          | F<br>(mm/min) | Ap<br>(mm) | S<br>(rpm)          | F<br>(mm/min) | Ap<br>(mm) | S<br>(rpm)             | F<br>(mm/min) | Ap<br>(mm) | S<br>(rpm)             | F<br>(mm/min) | Ap<br>(mm) | S<br>(rpm)      | F<br>(mm/min) | Ap<br>(mm) |
| 0.5mm- 2E                     | 25,200                                                                              | 270           | 0.045      | 25,200              | 135           | 0.038      | 18,900                 | 45            | 0.019      | 13,500                 | 27            | 0.009      | 25,200          | 360           | 0.049      |
| 0.5mm- 4E                     | 21,600                                                                              | 180           | 0.021      | 21,600              | 90            | 0.018      | 16,200                 | 27            | 0.009      | 13,500                 | 27            | 0.009      | 21,600          | 225           | 0.023      |
| 1.0mm- 6E                     | 18,000                                                                              | 540           | 0.07       | 17,100              | 450           | 0.06       | 10,800                 | 135           | 0.03       | 7,200                  | 45            | 0.014      | 18,000          | 630           | 0.07       |
| 1.0mm- 8E                     | 15,300                                                                              | 315           | 0.04       | 14,400              | 270           | 0.04       | 9,000                  | 90            | 0.02       | 7,200                  | 45            | 0.014      | 16,200          | 360           | 0.05       |
| 1.5mm- 8E                     | 10,800                                                                              | 315           | 0.1        | 9,900               | 270           | 0.08       | 6,300                  | 90            | 0.04       | 4,500                  | 45            | 0.021      | 11,700          | 360           | 0.11       |
| 2.0mm- 8E                     | 9,000                                                                               | 540           | 0.26       | 9,000               | 450           | 0.22       | 5,400                  | 135           | 0.11       | 3,600                  | 90            | 0.06       | 9,900           | 630           | 0.29       |
| 2.0mm- 10E                    | 7,200                                                                               | 315           | 0.24       | 8,100               | 270           | 0.2        | 4,500                  | 90            | 0.1        | 2,700                  | 45            | 0.05       | 8,100           | 360           | 0.26       |
| 2.0mm- 12E                    | 7,200                                                                               | 315           | 0.13       | 8,100               | 270           | 0.11       | 4,500                  | 90            | 0.06       | 2,700                  | 45            | 0.03       | 8,100           | 360           | 0.14       |
| 3.0mm- 08E                    | 6,300                                                                               | 540           | 0.36       | 6,300               | 450           | 0.3        | 4,500                  | 135           | 0.15       | 2,700                  | 90            | 0.08       | 7,200           | 630           | 0.39       |
| 3.0mm- 12E                    | 6,300                                                                               | 540           | 0.27       | 6,300               | 450           | 0.23       | 4,500                  | 135           | 0.11       | 2,700                  | 90            | 0.055      | 7,200           | 630           | 0.29       |
| 3.0mm- 16E                    | 6,300                                                                               | 315           | 0.2        | 5,400               | 270           | 0.17       | 3,600                  | 90            | 0.08       | 2,250                  | 45            | 0.04       | 6,300           | 360           | 0.22       |
| 3.0mm- 20E                    | 6,300                                                                               | 315           | 0.13       | 5,400               | 270           | 0.11       | 3,600                  | 90            | 0.05       | 2,250                  | 45            | 0.025      | 6,300           | 360           | 0.14       |
| 4.0mm- 16E                    | 4,500                                                                               | 540           | 0.36       | 4,500               | 450           | 0.3        | 2,700                  | 135           | 0.15       | 1,800                  | 90            | 0.075      | 4,500           | 630           | 0.39       |
| 4.0mm- 20E                    | 4,500                                                                               | 315           | 0.34       | 3,600               | 270           | 0.28       | 1,800                  | 90            | 0.14       | 900                    | 90            | 0.07       | 4,500           | 360           | 0.36       |
| 5.0mm- 20E                    | 3,600                                                                               | 450           | 0.45       | 3,150               | 450           | 0.38       | 1,800                  | 135           | 0.19       | 1,800                  | 90            | 0.09       | 3,600           | 540           | 0.49       |
| 5.0mm- 30E                    | 2,700                                                                               | 270           | 0.33       | 2,700               | 180           | 0.28       | 1,800                  | 135           | 0.14       | 1,800                  | 90            | 0.07       | 2,700           | 270           | 0.36       |
| 切削量<br>Cutting Amount<br>(mm) |  |               |            |                     |               |            |                        |               |            |                        |               |            |                 |               |            |

- 當加工聲音尖銳時，請調降主軸轉速(S) (10~40%)。 When the sound is piercing, please lower the spindle speed(S) (10~40%).
- 當機台震動太大時，請調降進給速度(F) (10~40%)。 When the machine is vibrating, please decrease the feed rate(F) (10~40%).
- 當主軸負載太大時，請調降進給速度(F) (10~40%)。 When the spindle load is high, please decrease the feed rate(F) (10~40%).
- 以上數據為建議值，適當的條件仍需視機台狀況，夾治具品質，潤滑冷卻系統...等而改變。  
These are recommended values which depend on the condition of the machine, fixture, lubricating & cooling systems... etc. They may have to be adapted.